

UNITED STATES PATENT APPLICATION

FOR

**METHOD OF FORMING HSQFN TYPE PACKAGE**

Inventors: Johnson C. H. Tzu; Hsu Po  
Chih; Jerry Y. J. Wu; and Jung Yu Lee

Prepared By:  
BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN  
12400 Wilshire Boulevard  
Seventh Floor  
Los Angeles, California 90025-1026  
(425) 827-8600

"Express Mail" mailing label number: EL431686275US

Date of Deposit April 9, 2001

I hereby certify that I am causing this paper or fee to be deposited  
with the United States Postal Service "Express Mail Post Office to  
Addressee" service on the date indicated above and that this paper  
or fee has been addressed to the Assistant Commissioner for  
Patents, Washington, D. C. 20231

Sharon E. Farnus

(Typed or printed name of person mailing paper or fee)

Sharon Farnus 4/9/01

(Signature of person mailing paper or fee) (Date signed)

## Field of the Invention

Sub 32 > 5

[illegible]

Sub B3

Sub B3  
digital systems and the desire to pack greater functionality into smaller spaces. Therefore, the number of a package's leads becomes more and more. An issue is that the package must have the capability to  
5 spread the heat generated by the die, efficiently.

---

Sub B4  
10 For assembling a semiconductor device, a semiconductor chip is properly positioned against the lead frame thus formed, then attached to the insulating film by heat and pressure. Next, the inner leads and their corresponding contact pads are electrically connected by bonding wires using a bonding tool, respectively. Finally, the inner leads and the semiconductor chip are covered by a molding  
15 resin to expose the outer leads of the lead frame from the molding resin.

---

Sub B5  
20 United States Patent 6,118,173 to Emoto, entitled "Lead frame and a semiconductor device". The package includes a chip, inner leads reaches the periphery of the semiconductor chip, and bonding wires for electrically connecting the semiconductor chip and the inner leads. The semiconductor chip is fixed on a die pad portion, and a chip fixing inner  
25 lead is integrated with the die pad portion. To

Sub B5  
simplify the bonding wire connection process and improve the reliability, the chip fixing inner lead has a step portion so that the die pad portion is formed at a lower position than the inner leads.

5 Further, United States Patent 6,107,675 disclosed a lead frame structure.

---

Sub B6  
10 One of the package types is so called QFP (Quad flat package), the QFP is the type used in logic and microprocessor packing that requires up to approximately hundreds pins. The semiconductor memory devices are designed to terminals (leads) for external connection as short as possible in order to make it possible to operate the devices at a higher speed such as the QFN (Quad Flat Non-leaded package).  
15 The QFN has a high-speed-oriented package structure in which no leads are provided but electrode pads for soldering are provided to a resin package.

---

20

### Summary of the Invention

Sub B7  
~~The object of the present invention is to provide a package with easier process and improved thermal dissipation.~~

---

Sub B8  
25 ~~A method of forming a HSQFN (High Stand-off Quad Flat Non-leaded) package comprising Providing a~~

Sub B8  
leadframe with bonding pads and die pads for receiving  
a die. Then, the die is attached on the die pad and  
bonding wires are connected between the bonding pads  
and the die for electrical connection. Molding  
5 process is used to encompass the die by compound from  
a first surface of the leadframe. Then, backside  
etching is used to the leadframe from a second surface  
of the leadframe to expose a lower surface of the  
compound, thereby separating the bonding pads and the  
10 die pads. A sigulation is applied to separate each  
individual package by cutting the leadframe and the  
compound.

Brief Description of the Drawings

Sub B9  
15 FIGURE 1 is a cross section view of a step of  
forming die pad and bonding pad according to the  
present invention.

Sub B10  
20 FIGURE 2 is a cross section view of a step of  
bonding die on a die pad according to the present  
invention.

FIGURE 3 is a cross section view of a step of  
bonding wires according to the present invention.

FIGURE 4 is a cross section view of a step of  
25 molding according to the present invention.

FIGURE 5 is a cross section view of a step of backside etching according to the present invention.

FIGURE 6 is a cross section view of a step of separating according to the present invention.

5

Detailed Description of the Preferred Embodiment

Sub  
B.11

10 The present invention discloses a method for a High Stand-off Quad Flat Non-leaded package technology. A package in accordance with the invention will be described in conjunction with and illustrative embodiment of the invention. Please referring to FIGURE 6, the structure of the HSQFN (High Stand-off Quad Flat Non-leaded) includes a leadframe having a die pad 62 and bonding pads 60. The die pad 62 and bonding pads 60 are the portions of the leadframe. The several die pad 62 straightly elongated in parallel relationship to each other from the frame body. The die pad 62 is designed to carry the die 64 adhesived thereon by adhesive material 63.

15

20 A number of bonding pads 60 formed on the lower surface of the package, and the die 66 is connected to the bonding pads 60 of the lead frame via a plurality of bonding wires 68 for electrical communication. Molding compound 70 encompasses the entire die 66, the

25 bonding wire 68 and the major portion of the lead

Sub B11  
frame, leaving the terminal of the inner lead exposed out of the body. According to the structure of the present invention, not only the die pad is exposed, but also the lower surface of the bonding pad 60 is exposed. This structure provides excellent thermal dissipation from the packages.

Sub B12  
Two stages of etching are used to etch the upper surface (first side) and lower surface (second surface), respectively. The method comprises performing die bonding, wire bonding and molding between two stages of etching. Wherein a first etching of the two stages of etching comprises forming an inward indentation portion of the leadframe from a first side of said leadframe to define die pads and bonding pads. A second etching of the two stages of etching comprises separating the die pads and bonding pads by etching from a second side of the leadframe.

Sub B13  
20 The method for forming the package includes preparing a lead frame having a die pad 62 to receive a die 64, as shown in FIGURE 1. This present invention can be achieved by using "stand off" method. In one preferred embodiment, please refer to FIGURE 1, the upper surface (the first surface) of the lead frame

Sub B13 is etched to form a plurality of inward indentation portions 61. Alternatively, the inward indentation portions 61 may be formed by external force punch.

Sub B14  
5 Next, the die 64 is bonded on the die pad 62 by adhesive material such as silver epoxy 63, as shown in FIGURE 2. Subsequently, bonding wires 68 are bonded to connect the die 66 and the connecting pads or bonding pads 60, as illustrated in FIGURE 3.  
10 Preferably, wire bonding technique is carried out to form the bonding wires for constructing the communication path between the die 66 and the external circuits. The bonding technique is well known in the art, the detailed description is omitted.

15

Sub B15  
Turning to FIGURE 4, the die is encapsulated by mold resin 70. To phrase in another way, molding compound is injected into a mold to form a shielding to protect the die 64 from being damaged by external  
20 force. Please turn to FIGURE 5, thereafter, PMC (post molding curing) step is performed, this is well known in the art, detailed description is unnecessary. Next, a backside etch is utilized to separate the connection between the die pads 62 and the bonding  
25 pads 60. This can be achieved by using lithography and



Sub B'15  
etching process to etch the leadframe from the second surface of the leadframe, thereby exposing the lower surface of the mold resin 70. Other method may be used, as shown in FIGURE 5. The etched portions of the 5 leadfram are aligned to the inward indentation portions of the first surface.

Sub B'16  
Referring to FIGURE 6, a sigulation step is performed to separate each individual package. 10 Therefore, the package is cut at specific portions. Optionally, solder ball may be formed on the terminal of the bonding pads.

Sub B'17  
The benefits of the present invention includes the improvement of heat dissipation characteristic. The die pad which is a portion of the leadfeame is exposed to enhance the thermal dissipation.

Sub B'18  
As is understood by a person skilled in the art, the foregoing preferred embodiments of the present invention are illustrated of the present invention rather than limiting of the present invention. It is intended to cover various modifications and similar arrangements included within the spirit and scope of 25 the appended claims, the scope of which should be

accorded ~~the~~ broadest interpretation so as to encompass all such modifications and similar structure. Thus, while the preferred embodiment of the invention has been illustrated and described, it

5 will be appreciated that various changes can be made therein without departing from the spirit and scope of the invention.

---

Sub  
B<sup>18</sup>

106040 50562860